
DOOR BOTTOM SEALS

LAS3001 si

MORTISED 32dB

The LAS3001 si door bottom seal is a practical and efficient solution designed to enhance the acoustic containment of your door. Fitted with a slide-in gasket, this seal provides a dependable barrier that minimises sound transmission, helping to create a quieter and more comfortable space.

ID No. 350



LAS3001 si



LAS3001 si (shown with LAS4001)

SYSTEM SPECIFICATIONS

Test evidence
- Acoustic: BS EN ISO 10140-2: 2010. Rw 32dB.

Characteristics
- Contributes towards smoke, weather, draught, and light containment when fitted with a suitable threshold seal.

Location
- Single and double swing doors.

Use with
- Practically any threshold plate.

Min/max gap size
- 6mm/13mm.

Seal material
- Flexible silicone rubber.

Standard lengths
- 1m and 2.1m. Other lengths to special order.

Fixing
- Face-fixed, semi-rebated or fully rebated.
- Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request).
- Fixing holes are pre-drilled. Once the aluminium carrier is fixed, the flexible silicone rubber gasket slides easily into place.
- Note: these seals cannot be adjusted once fitted.

Finish
- Silver anodised aluminium with grey silicone insert.

Certification

(R27972)

T: +44 (0)1626 834252
E: mktg@lorientuk.com

LORIENT
ASSA ABLOY